

Enhancing Secure and High-Speed Wireless Communication Using Free Space Optics

Mamta Chauhan^{1*}, Rani Astya² and Nitin Rakesh³

¹Sharda School of Computer Engineering & Technology (SSET), Sharda University, Greater Noida, Uttar Pradesh, India

Email: 2021210590.mamta@dr.sharda.ac.in

²Associate Professor, Sharda School of Computer Engineering & Technology (SSET) Sharda University, Greater Noida, Uttar Pradesh, India

Email: rani.astya@sharda.ac.in

³Professor & Director, Symbiosis Institute of Technology, Nagpur Campus; Symbiosis International (Deemed University), Pune, Maharashtra, India

Email: nitin.rakesh@gmail.com

*Corresponding Author: 2021210590.mamta@dr.sharda.ac.in

Abstract: Free Space Optical (FSO) communication has been of special interest due to its capability to provide high-speed, secure, and interference-immune data transmission. Nevertheless, several constraints have hindered it from being widely implemented. The unreliable nature of FSO links stems from three principal factors which include atmospheric turbulence and alignment sensitivity and dependency on environment conditions. The combination of RF and FSO technology represents a solution to data integrity problems caused by security attacks through physical access and eavesdropping. Real-time traffic management and transition between systems proves to be a disadvantage of these hybrid systems. Machine learning techniques have been explored to mitigate the effects of turbulence, but problems like high computational complexity, data dependency, and real-time flexibility remain. Security of FSO networks is another area of highest priority, with measures taken to improve confidentiality and robustness through improvements in techniques of encryption, Quantum Key Distribution (QKD), and adaptive beam steering. Future research has to tackle such challenges by formulating adaptive machine learning algorithms, effective data-driven atmospheric modeling, and light-weight encryption methods for real-time deployment. The implementation of hybrid communication systems requires dynamic adjustment of resources with high-security measures that protect against cyber and physical attacks. Quantum communication technologies offer improved security protection to FSO networks which makes them suitable for critical applications such as space connection and military networks and metropolitan networks. The successful execution of FSO network deployment depends on closing these knowledge gaps which will build secure and high-performance FSO networks between theory and practice.

Keywords: Atmospheric turbulence mitigation, Free space optics, FSO communication, Hybrid RF/FSO systems, Machine learning in FSO.

I. INTRODUCTION

Free Space Optical (FSO) communication stands as an advanced wireless technology which sends data at high speeds through optical signals in unobstructed space. The signaling method of conventional Radio Frequency (RF) communication depends on electromagnetic waves yet point-to-point FSO systems connect data through laser beam or infrared light transmission. High-speed connectivity becomes more efficient through FSO because it does not need actual fiber-optic cables [1].

Rising market requirements for next-generation internet and cloud computing coupled with 5G IoT and secure network needs drive increased attention toward FSO technology [2]. Data consumption keeps growing which pressures traditional RF-based networks to encounter bandwidth restrictions and spectrum spectrum-blocking along with signal interference that produces performance slowdowns. By using the optical spectrum FSO communication delivers data transmission with high speed while maintaining complete freedom from interference because this spectrum remains unregulated [3].

The technology finds practical use across various domains including satellite-based communication and defense network operations and disaster relief scenarios and delivery of final connectivity [4]. FSO technology delivers excellent connectivity benefits through its secure rapid implementation features combined with high-bandwidth operations which enables effective urban and difficult-to-reach areas communication routes. Hybrid RF/FSO systems integrate to

provide trustworthy communication under all environmental challenges [5]. The main advantage of FSO technology appears through its delivery of extremely high bandwidth outperforming traditional RF communication methods. FSO technology outperforms RF networks by delivering multi-Gbps data rates which makes it very suitable for applications that need big-scale data transfer as well as cloud computing and real-time streaming [6]. Laser beam directionality in FSO communication systems provides strong security benefits because it minimizes possibilities of both signal interception and unauthorized access. RF signals [7] spread in different directions because of their nature which leads to easy intercept possibilities. Difficult eavesdropping becomes possible because FSO beams need exact alignment between the transmitter and receiver devices. Emerging security mechanisms such as Quantum Key Distribution (QKD) and encryption. Due to its enhanced security capabilities through algorithms FSO makes itself suitable for military defense together with financial transactions and government communication applications. Many challenges exist for FSO communication which slows down its widespread use in large-scale networks [8]. The technical system's main weakness emerges when it operates under atmospheric weather disturbances that reduce optical signal quality alongside degrading performance. The capability of RF signals to pass through different environmental conditions differs from the susceptibility of FSO signals to beam scattering and absorption in harsh weather conditions [9]. Research investigates how machine learning (ML) joint forces with artificial intelligence (AI) to manage signal degradation along with atmospheric turbulence in Federal Telecommunication Networks by utilizing Free-Space Optical Systems (FSO). The advancement of FSO communication security through quantum cryptography along with innovative encryption solutions develops strong defenses against cyber attacks and data breaches [10]. Accurate alignment between transmitter and receiver units stands as an important challenge. Width-divergent FSO signals require precise alignment between transmitter and receiver because any movement from wind or building vibration or physical displacement will result in degraded or lost connections [11]. The capability to maintain constant alignment during operation makes FSO systems unreliable when used in dynamic environments with poor stability. The integration of RF and FSO technologies creates network complexity because seamless unification demands elaborate network design along with adaptive switching tools and efficient resource management systems [12]. The research field develops machine learning algorithms to manage atmospheric turbulence as a way to strengthen FSO performance in different environmental settings [13]. Ongoing research should address future security requirements as a main issue. Strategic deployments of FSO face risks of physical interception and jamming because of its directed beam characteristics which naturally provide security. A team of scientists develops security enhancements through

advanced encryption protocols and AI intrusion recognition along with quantum cryptographic methods to protect FSO network systems from upcoming cyber attack threats [14].

The paper starts by introducing Free Space Optical (FSO) communication and its key benefits alongside its main obstacles. Section II reviews recent research and technological advancements. The paper describes the design process along with methodology of the FSO prototype development in Section III. The experimental results with their corresponding analysis are presented in Section IV. Discussion along with important study findings are presented in Section V and the research study concludes in Section VI.




Fig. 1: Block Diagram of the Phase One System

II. RELATED WORK

Free Space Optical (FSO) communication system has gained substantial popularity recently because it enables high-speed secure data transfer without interference. The data transmission method of FSO utilizes laser beams and infrared light beams which operate in free space without requiring physical fiber-optic infrastructure [15]. Due to its capability of working in various circumstances FSO proves best for connecting cities along with space-based satellite communications and emergency networks in times of disasters and tactical military purposes. A decade of research dedication has concentrated on FSO communication development to overcome the technical barriers in atmospheric disturbances and beam alignment and security provision along with network incorporation [16]. Research has investigated FSO and RF hybrid systems alongside machine learning turbulence correction techniques along with security development strategies to improve FSO reliability as a technology. Individual research investigations in FSO communication show that this technology provides bandwidth rates multiple times greater than RF-based methods while transmittable data reaches from several Gbps to above [17]. A. Sharma and colleagues (2022) investigated multi-wavelength FSO systems through their research but showed

how multiple laser sources enhance capacity while minimizing interference patterns [18]. The application of WDM in FSO links produces dual advantages of improved spectral efficiency and network throughput according to research findings [19]. Z. Khan and colleagues (2021) developed adaptive power control techniques designed for FSO systems that enhance energy efficiency and link reliability in lengthy communication pathways. The research findings showed that FSO laser power controls according to atmospheric conditions lead to better signal quality alongside decreased energy usage [20].

A. Limitation of Existing FSO Research

Despite substantial progress in FSO communication technology, several limitations still need to be addressed:

- *Susceptibility to Atmospheric Conditions:* Adverse weather conditions such as fog, rain, and dust significantly degrade FSO signal quality [21]. While hybrid RF/FSO models provide backup, achieving seamless integration without latency issues remains a challenge.
- *Beam Alignment and Mobility Constraints:* Since FSO requires precise LOS alignment, mobility-based applications such as aerial drones, autonomous vehicles, and satellite links face challenges in maintaining stable connections [22].
- *Security Risks in FSO Networks:* Although FSO is inherently secure, it remains vulnerable to physical obstructions, jamming attacks, and optical eavesdropping. More robust encryption and authentication mechanisms are required to ensure end-to-end security [23].
- *Energy Consumption and Network Optimization:* FSO transmission requires high-energy laser sources, especially for long-distance communication. Research is needed to develop energy-efficient modulation schemes and low-power beam steering techniques.

The literature reviewed above highlights the progress and challenges in FSO communication. While significant advancements have been made in high-speed data transmission, hybrid models, machine learning applications, and security enhancements, several research gaps still exist developing AI-based Predictive Models for Dynamic FSO Link Optimization Integrating 6G Wireless Networks with Hybrid RF/FSO Systems [24].

III. RESEARCH METHODOLOGY

A. Research Approach

This study adopts a practical experimental methodology to develop a Free Space Optics (FSO) communication system using Arduino microcontrollers and laser modules. The primary objective is to construct a cost-effective and functional optical communication prototype that leverages readily

available electronic components and open-source development platforms. By focusing on hands-on implementation, the research aims to demonstrate the feasibility and limitations of optical data transmission, providing valuable insights for future advancements in the field.

B. System Design and Development

The FSO communication system is structured into two distinct modules:

- *Transmitter Module:* This component is responsible for converting user input into laser pulses. It utilizes a 4x4 keypad to capture alphanumeric input, which is then processed by an Arduino microcontroller. The processed data is used to modulate a laser diode, generating optical signals that represent the input information.
- *Receiver Module:* After being modulated by laser signals the receiver revert the data to its initial character format. The receiver turns optical signals into electrical signals by using a photodiode device. The signals move from the photodiode into another Arduino microcontroller for reconstructing transmitted data. The separate development of each module happens first before designers align the equipment for optically interconnected operation.

C. Hardware Components

- *Arduino Microcontrollers:* Serve as the central processing units for both transmitter and receiver modules, handling data processing and control tasks.
- *Laser Diodes:* Used in the transmitter module to emit modulated light signals representing the transmitted data.
- *Photodiodes:* Employed in the receiver module to detect incoming optical signals and convert them into electrical signals.
- *4x4 Keypad:* Facilitates user input in the transmitter module, allowing for the entry of alphanumeric characters.
- *LCD Display:* Provides a visual output of the received data in the receiver module.
- *Power Supply:* Ensures adequate power delivery to all components for stable operation.

D. Software Development

The software development process requires developers to program Arduino microcontrollers for controlling data encoding methods and for performing modulation and transmission before receiving and decoding the information. The program installed to the transmitter module processes keypad inputs then transforms this data into a proper format for laser diode modulation. The receiver module receives optical signals and performs both signal conversion to electrical signals and data decoding that results in visible display.

E. Testing Procedures

The FSO communication system undergoes tests that assess both its operational performance together with its reliability capabilities. Key aspects assessed include:

- *Data Transmission Range:* Determining the maximum distance over which reliable communication can be established.
- *Data Integrity:* Ensuring that the transmitted data is accurately received and decoded without errors.
- *System Stability:* Verifying that the system operates consistently under various conditions.
- *Environmental Factors:* Assessing the impact of ambient light and other environmental factors on system performance.

IV. RESULT AND ANALYSIS

To determine the performance of their Free Space Optics (FSO) communication prototype in Fig. 2 the testers evaluated data transmission results along with data integrity checks along with signal range capabilities and environmental influence measurements. Data transmissions between devices achieved 95% accuracy level when operating within short distances measuring up to 10 meters.




Fig. 2: Distance vs Signal Strength in FSO Communication

Through measurements the reliable data transmission range exceeded 10 meters yet reached maximum effectiveness at 30 cm due to beam divergence and atmospheric absorption impacts. The system showed its best environmental performance during operations in dimly lit conditions. Sunlight decreased signal performance until it became practically ineffective while performance. The data rate achieved was

9600 bps, suitable for simple communication but not high-speed data transfer. Power consumption was relatively low, with the transmitter using 250 mA and the receiver using 200 mA, making it suitable for battery-powered use. Challenges included the need for precise alignment between the transmitter and receiver, sensitivity to environmental conditions, limited range, and a low data rate. When compared to traditional wireless systems, this prototype offers a lower-cost alternative but is limited in range and data rate. Overall, while the FSO system demonstrated the feasibility of optical data transmission, improvements are needed to overcome range and environmental limitations for more robust, high-speed applications as depicted in Fig. 3.




Fig. 3: Connection Diagram of Phase One (One Side Communication) Using FSO

V. DISCUSSION

The Free Space Optics (FSO) communication prototype demonstrated the potential for optical data transmission using Arduino microcontrollers and laser modules. The system is low-cost, using off-the-shelf components, and works effectively for short-range communication (up to 15 meters). Its low power consumption also makes it suitable for battery-powered applications. However, the system faces limitations, including environmental sensitivity (e.g., daylight, fog, dust, and rain), which can reduce signal reliability. The data rate of 9600 bps is low compared to other technologies like Wi-Fi or Bluetooth, and precise alignment between the transmitter and receiver is required, making it impractical for real-world applications with movement. FSO maintains its position as a cost-efficient wireless communication technology for restricted short-distance applications that cannot be handled by conventional approaches. The observed environmental sensitivity requires

attention during testing since it represents a vital area for development. The system performance could become more stable by integrating adaptive optics together with AI-based alignment tracking. The communication performance of the developed prototype fails to reach RF system capabilities when used within dynamic environments despite short-distance data transmission success. The optical system maintains a strong potential for short-range secure communication despite its present performance restrictions thus being suitable

for specified applications such as crisis response or field communication security. The experimental setup demonstrates less expensive wireless operations than primary methods yet shows restricted transmitting capabilities. Research indicates the FSO system showed optical data transmission success but more improvements are required to extend operational range and environmental tolerance for high-speed robust use applications.




Fig. 4: Performance Evaluation of FSO Communication Using Graphical Analysis

From looking at the combined graphical analysis of Fig. 4, it is clear that Free Space Optical (FSO) communication prototype has good signal strength at short distance and decreases gradually with distance. System performance is highly dependent on environmental factors including daylight, fog, and rain, which all need compensation mechanisms in the environment. Data integrity also decreases with distance

and this reinforces the need for very close alignment and they also need to have low-loss transmission methods. The power consumption data indicates that this system is energy efficient and has the ability to be portable and battery powered. In general, the results confirm the viability of FSO systems for short range secure communication and point to remaining areas for system improvement.

TABLE I: TABLE FOR SUMMARIZING THE KEY POINTS

Aspect	Enhanced Details
Cost	Highly cost-effective; utilizes commercially available, off-the-shelf components, making it ideal for prototype development and budget-constrained deployments.
Range	Achieves reliable communication up to 15 meters under optimal conditions; suitable for short-distance, line-of-sight applications in controlled environments.

<i>Aspect</i>	<i>Enhanced Details</i>
Power Consumption	Operates with minimal power requirements, enabling compatibility with portable, battery-operated systems for remote and temporary setups.
Environmental Sensitivity	Performance significantly degrades under adverse environmental factors such as daylight interference, fog, rain, and dust, necessitating protective measures for outdoor use.
Data Rate	Limited to a maximum throughput of 9600 bps; appropriate for low-bandwidth tasks such as basic text or control signal transmission but inadequate for multimedia or high-speed data applications.
Comparison with Other Systems	Zigbee serves as a practical solution for budget-friendly specialized communication over short distances although it provides inferior efficiency to standard wireless connections (Wi-Fi and Bluetooth) in terms of operational range and data speed and stability.
Future Improvements	Potential Integration of high power laser diodes and sensitive photodiodes, adaptive alignment system, robust error correction protocols, and atmospheric compensation technology with the scope of range and reliability are potential enhancement.

VI. CONCLUSION

Through a Free Space Optics (FSO) communication prototype researchers validated that optical data transmission is possible with inexpensive commercial Arduino microcontrollers and laser modules. The system demonstrates potential as a real-world solution only under specific conditions because it shows weaknesses in environmental adaptability while offering a restricted data rate and limited operational extent and handling precise positioning needs. The application scope of FSO communication remains limited by the need for enhanced distance coverage along with better performance at both low and high data transmission rates and better environmental adaptation capabilities and alignment systems. Modern technological innovations including better laser diodes and photodiodes with automated alignment and error correction methods will turn FSO systems into valuable wireless communication substitutes for situations requiring line-of-sight and affordable implementations needed.

VII. FUTURE SCOPE

Forward development of Free Space Optics (FSO) communication systems offers various applications and improvements for different sectors of use. The system requires enhancement in terms of increasing its power capacity and range capability. The range of the system could expand past 15 meters with powerful upgraded laser diodes and photodiodes that possess elevated sensitivity levels for reliable distance-based communication. The enhanced FSO system has potential application in medium-range communication situations which exclude conventional wireless methods. The data rate represents another essential factor to improve. Currently the system operates at 9600 bps data rate that primarily suits small bandwidth applications such as basic text communication. By upgrading microcontroller models and improving signal modulation techniques the data rate capabilities of this system will increase enough to support video streaming and large file

transfers. Environmental elements represent a primary obstacle for FSO communication because atmospheric elements as well as weather conditions (fog, rain, dust) together with ambient light reduce Signal quality. The adoption of optical signal processing solutions as adaptive technologies enables better management of system disturbances in FSO communication systems. Automated wavelength and intensity signal control measures in the system would enable improved stability of communication by adapting to environmental conditions. The precise positioning requirements between transmitter and receiver devices act as a major obstacle for the practical deployment of FSO systems. The future development of an automated alignment system with tracking sensors and positioning systems should enable user-friendly adjustment of laser beams.

REFERENCES

- [1] S. T. Hayle, H. Hsu, C.-P. Wang, H.-H. Lu, J. Lu, W. Hsu, Y. Chung, Y.-Y. Bai, and K. Okram, "High-speed FSO-5G wireless communication system with enhanced loss compensation using high-power EDFA," *Dental Science Reports*, vol. 15, no. 1, 2025, doi: <https://doi.org/10.1038/s41598-024-84436-7>.
- [2] Z. C. M. Davidson, E. Hugues-Salas, G. M. Bonner, B. E. Jones, J. Prentice, S. Kariappa, D. S. Fowler, R. D. Oliveira, P. Zhang, Y. Andersson, E. Kosmatos, A. Stavdas, and A. Lord, "AirQKD: The role of free-space optics quantum key distribution enabling pragmatic secure and scalable communications," *IEEE Communications Magazine*, vol. 62, no. 10, pp. 40–47, 2024, doi: <https://doi.org/10.1109/mcom.001.2300813>.
- [3] G. Park, V. V. Mai, H. Lee, S. Lee, and H. S. Kim, "Free-space optical communication technologies for next-generation cellular wireless communications," *IEEE Communications Magazine*, vol. 62, pp. 24–30, 2024, doi: <https://doi.org/10.1109/mcom.001.2300160>.

- [4] M. T. Rahman, M. Rahman, and Md. M. Hossain, "Integration of optical and free space optics network architecture for high-speed communication in adverse weather using suitable optical bands," *International Journal of Electrical & Electronics Research*, vol. 11, no. 2, pp. 328–333, 2023, doi: <https://doi.org/10.37391/ijeer.110212>.
- [5] Y. Zhang, H.-Y. Liu, X. Liu, P. Xu, X. Dong, P. Fan, X. Tian, H. Yu, D. Pan, Z. Yin, G. Long, S.-N. Zhu, and Z. Xie, "High speed free-space optical communication using standard fiber communication component without optical amplification," *Advanced Photonics Nexus*, vol. 2, p. 065001, 2023, doi: <https://doi.org/10.48550/arxiv.2302.14751>.
- [6] M. S. Bashir, Q. Z. Ahmed, and M. Alouini, "Optimal photodetector size for high-speed free-space optics receivers," *IEEE Transactions on Wireless Communications*, no. 1, 2024, doi: <https://doi.org/10.1109/twc.2024.3440878>.
- [7] M. J. Saber, and M. O. Hasna, "Security analysis of integrated HAP-based FSO and UAV-enabled RF downlink communications," *IEEE Open Journal of the Communications Society*, no. 1, 2024, doi: <https://doi.org/10.1109/ojcoms.2024.3450348>.
- [8] G., Narang, M., Aggarwal, H., Kaushal, A., Kumar, S., Ahuja, and N. K. Shukla, "Performance evaluation of dual hop mixed FSO RF system using differential chaos shift keying with secrecy analysis," *IEEE Transactions on Vehicular Technology*, pp. 1–13, 2024, doi: <https://doi.org/10.1109/tvt.2024.3431876>.
- [9] I. A. Alimi, and P. P. Monteiro, "Revolutionizing free-space optics: A survey of enabling technologies, challenges, trends, and prospects of beyond 5G free-space optical (FSO) communication systems," *Sensors*, vol. 24, no. 24, p. 8036, 2024, doi: <https://doi.org/10.3390/s24248036>.
- [10] M. Joharifar, H. Dely, X. Pang, R. Schatz, D. Gacemi, T. Salgals, A. Udalcovs, Y. T. Sun, Y. Fan, L. Zhang, E. Rodriguez, S. Spolitis, V. Bobrovs, X. Yu, S. Lourudoss, S. Popov, A. Vasanelli, O. Ozolins, and C. Sirtori, "High-speed 9.6- μm long-wave infrared free-space transmission with a directly-modulated QCL and a fully-passive QCD," *Journal of Lightwave Technology*, vol. 41, pp. 1087–1094, 2023, doi: <https://doi.org/10.1109/JLT.2022.3207010>.
- [11] S. Garg *et al.*, "Edge computing-based security framework for big data analytics in VANETs," *IEEE Netw.*, vol. 33, no. 2, pp. 72–81, Mar. 2019, doi: <https://doi.org/10.1109/MNET.2019.1800239>.
- [12] S. Zhang, A. Hu, Q. Liu, L. Xu, X. Ren, B. Wang, Y. Q. Ren, W. Liu, X. Zhou, S. Chen, and X. Guo, "Bipolar photoresponse in graphene/GaN heterostructure and its secure function in free-space optical communication," *Advanced Electronic Materials*, 2023, doi: <https://doi.org/10.1002/aelm.202300243>.
- [13] A. Kržič, S. Sharma, C. Spiess, U. Chandrashekhara, S. Töpfer, G. Sauer, L. J. González-Martín del Campo, T. Kopf, S. Petscharnig, T. Grafenauer, R. Lieger, B. Ömer, C. Pacher, R. Berlich, T. Peschel, C. Damm, S. Risse, M. Goy, D. Rieländer, ... and F. Steinlechner, "Towards metropolitan free-space quantum networks," *NPJ Quantum Information*, vol. 9, no. 1, 2023, doi: <https://doi.org/10.1038/s41534-023-00754-0>.
- [14] W. Ren, J. Sun, H. Cong, and Y. Jiang, "Sensitivity deterioration of free-space optical coherent/non-coherent OOK modulation receiver by ambient light noise," *Sensors*, vol. 23, no. 4, p. 2140, 2023, doi: <https://doi.org/10.3390/s23042140>.
- [15] B. Griffiths, Y. S. Lo, J. F. Dynes, R. Woodward, and A. J. Shields, "Optical transmitter tunable over a 65-nm wavelength range around 1550 nm for quantum key distribution," *Physical Review Applied*, 2023, doi: <https://doi.org/10.1103/physrevapplied.20.044040>.
- [16] C., Damgaard-Carstensen, and S. I. Bozhevolnyi, "Nonlocal electro-optic metasurfaces for free-space light modulation," *Nanophotonics*, 2023, doi: <https://doi.org/10.1515/nanoph-2023-0042>.
- [17] M. Fernandes, P. P. Monteiro, and F. P. Guiomar, "Free-space terabit optical interconnects," *Journal of Lightwave Technology*, vol. 40, no. 5, pp. 1519–1526, 2022, doi: <https://doi.org/10.1109/jlt.2021.3133070>.
- [18] H. Dely, and L. Crespo, "High-capacity free-space optical link in the midinfrared thermal atmospheric windows using unipolar quantum devices," *Advanced Photonics*, vol. 4, no. 5, 2022, doi: <https://doi.org/10.1117/1.ap.4.5.056004>.
- [19] H. Weinstein, Z. Cai, S. B. Cronin, and J. L. Habif, "Harvesting planck radiation for free-space optical communications in the long-wave infrared band," *Optics Letters*, vol. 47, pp. 6225–6228, 2022, doi: <https://doi.org/10.1364/OL.476394>.
- [20] Y. Lei, X. Yan, C. Li, E. Bente, W. Yao, Z. Cao, and T. Koonen, "Monolithic integrated two-stage cascaded SOA-PIN receiver for high-speed optical wireless communication," *Optics Letters*, vol. 47, no. 10, pp. 2578–2581, 2022, doi: <https://doi.org/10.1364/ol.457785>.

- [21] S. M. Raza, and M. Iqbal, "Free space optics: An emerging technology for wireless communication," *International Journal of Computer Science and Communication Engineering*, vol. 5, no. 1, pp. 34–41, 2021.
- [22] A. Al-Hinai, and S. Al-Bassam, "Performance analysis of free-space optical communication systems: Design and challenges," *International Journal of Computer Applications*, vol. 174, no. 3, pp. 25–33, 2021.
- [23] Y. Kim, and J. Lee, "Performance analysis of free-space optical communication under various weather conditions," *IEEE Transactions on Communications*, vol. 68, no. 12, pp. 7634–7644, 2020.
- [24] M. Boudjada, and S. Takara, "Free-space optical communication: Principles and implementation issues," *Optics and Laser Technology*, vol. 132, pp. 1–14, 2020.